

K JOINT

Joint Compound



K JOINT

Easy Finish, Multi Purpose Joint Compound

General Information

- > Easy to mix and apply smoothly.
- > Flexible for non-cracking joints.
- > One product for both filling and finishing.
- > Controlled working time for work sequencing.
- > Mix 2 parts of compound with 1 part of clean water for maximum coverage area.

Knauf Joint Compound

Knauf Joint Compound is a gypsum based product designed for filling and finishing gypsum board joints and screw heads. It has an optimum working time for bedding in joints by hand and saves time.

Special Formula Jointing Compound

Specially formulated for use with gypsum boards all gypsum repair work and leveling the surface prior to applying paint or wall paper.

Product Information KNAUF Joint Compound

Mixing Ratio (Gypsum: Water)	2:1
Working Time	90 minutes
Coverage Area	57 sq.m.
Shelf Life	9 months

Mixing Direction

Mix 2 parts of compound with 1 part of clean water. Mix together until consistently smooth with no lumps. Keep buckets and tools clean to avoid reduced working times.

Caution

Should not use in areas where temperature exceeds 45 degrees celcius or below zero degrees.

Storage

The bag should be tightly closed after use. Store above ground level in a dry place.



Mix Before use



Mixing Ratio



Setting Time
90 minutes



Coverage Area



Shelf Life

GENERAL INFORMATION



Easy to mix



No cracks



Strong adhesion



Easy to sand



1 Use clean container and tools. Add water first then add compound in ratio of 1 water + 2 joint filler, mix it well for about 2-3 minutes. Mix both until consistently smooth with no lumps



2 Apply the first coat of compound by using 4" trowel to apply then, or putty knife in tape (paper or cotton). Fill any gaps (screw) at the joint and allow compound to set or dry about 90 minutes.



3 When the compound has set hard, apply the second coat and third coat with finishing trowel and allow each coat to set. When the final coat has dried, the joints and screw heads should be lightly sanded before painting.



KNAUF VIETNAM



KNAUF'S HANOI OFFICE

Unit 6-7, 8th Floor, TNR Tower,
54A Nguyen Chi Thanh, Dong Da Dist.,
Hanoi

- > Tel: +84 24 3791 8412
- > Fax: +84 24 3791 8413



KNAUF'S HAIPHONG FACTORY

Plot CN4.4A, Dinh Vu Industrial Zone,
Dong Hai 2 Ward, Hai An District,
Dinh Vu-Cat Hai Economic Zone, Haiphong

- > Tel: +84 225 8830 666
- > Fax: +84 225 8830 686



KNAUF DIGITAL

- > Email: info@knauf.com.vn
- > www.facebook.com/knauf-vietnam-636398023062218
- > www.knauf.com.vn

Knauf Vietnam Co., Ltd.
Unit 6-7, 8th Floor, TNR Tower,
54A Nguyen Chi Thanh, Dong Da Dist.,
Hanoi, Vietnam



Knauf Singapore
www.knauf.com.sg

Knauf Indonesia
www.knauf.co.id

Knauf Thailand
www.knauf.co.th

Knauf Philippines
www.knauf.com.ph